

The Monimax 5300 is more than just a powerful, secure ATM. It also offers you more revenue opportunities with optional sidecars.

Features

Scalability and Flexibility

The Monimax 5300 supports up to 6,000 notes in three cassettes. Automated bill-payment, stored Value cards and check-cashing services with optional sidecars are all designed to maximize your revenue.

Multiple Pricing Options

We can design an ATM program that works well for you. Let's discuss the options.

Small Footprint

This sleek model is popular both on- and off-site because it has a small footprint that meets all ADA standards.

Add Optional, Powerful Sidecars

Two optional sidecars offers even more profitable features. The HK300 includes a bill acceptor, card printer and card dispenser. The HK400 includes a check scanner, finger-print scanner, coin dispenser, ID card scanner and card dispenser.

Superior quality, security and value.

Only with Nautilus Hyosung.

Now offering the most complete line of financial and retail ATMs.



The Monimax 5300 can grow with your business.

Dependable Customer Service

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.

MONIMAX 5300

System Control

- Intel® Pentium®-IV processor
- Microsoft® Windows® XP platform
- Optional 12.1" TFT LCD

Communication

- TCP/IP (SSL configurable) or Dial-up

Application Software

- NDC+
- DDC912

Customer Display

- 15" TFT LCD
- Optional sunlight viewable
- Optional touch screen

Input Type

- 4 x 2 function keys
- PCI EPP (Encrypting PIN pad)
- ADA compliant

Card Handling

- Dip-type card reader
- Optional IC card reader, EMV Level 1, 2

Cash Dispensing

- 2,000-note cassette
- Up to three cassettes (6,000 notes)

Printers

- 3.1" graphical thermal receipt printer
- Electronic journal

Security

- UL291 business hour safe
- Standard electronic safe lock
- Security camera
- Optional KABA Mas Cencon safe lock

Miscellaneous

- Guide lights
- Optional high-brightness topper

Power Supply

- AC 110–230V, 50–60 Hz
- Back-up battery (last transaction and shut-down)

Operating Environment

- Temperature: 32°F–104°F
- Humidity: 25%–85%

Dimension and Weight

- Height: 51.2" (1,060 mm)
- Width: 16.1" (410 mm)
- Depth: 22.8" (580 mm)
- Weight: 265 lbs (120 kg)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

Optional HK 300 Sidecar

Optional HK 400 Sidecar



Nautilus
HYOSUNG

Contact your authorized Nautilus Hyosung distributor or representative for more information.